diskontcomputer.com
Firma Matzner Michael e.U.
Traunuferstrasse 110
4052 Ansfelden, Austria

P67 Transformer

- ASRock DuraCap (2.5 x longer life time), 100% Japan-made high-quality Conductive Polymer Capacitors
- Supports Intel® Lynnfield Core™ i7 / i5 Processors in LGA1156 Package
- Supports Dual Channel DDR3 2600+(OC)
- 2 x USB 3.0 ports, 2 x SATA3 connectors, 1 x eSATA2 connector
- Dr. Debug, Smart Switch Design: Power/Reset/Clear CMOS Switch with LED
- Supports ASRock Extreme Tuning Utility (AXTU), XFast USB, UEFI, Instant Boot, Instant Flash, Good Night LED, APP Charger, SmartView
- Combo Cooler Option (C.C.O.)
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec), Premium Blu-ray audio support

  - Free Software : CyberLink DVD Suite - OEM and Trial; Creative Sound Blaster X-Fi MB - Trial

Dieses Modell wird möglicherweiße nicht weltweit verkauft. Bitte kontaktieren Sie ihren Händler für Informationen über die Verfügbarkeit in ihrerer Region.

ASRock P67 Transformer is amazing! It's the first P67 motherboard supporting Socket 1156 processors in the world. Clean/compact design is particularly a selling point as well. ASRock P67 Transformer received "Great Value Award" from PureOverclock.

Produkt Spezifikationen

Generelles	
CPU	- Supports Intel® Lynnfield Core™ i7 / i5 Processors in LGA1156 Package - Advanced V8 + 2 Power Phase Design - Supports Intel® Turbo Boost Technology - Supports Hyper-Threading Technology - Supports Untied Overclocking Technology
Chipsatz	- Intel® P67
Arbeitsspeicher	- Dual Channel DDR3 memory technology - 4 x DDR3 DIMM slots - Supports DDR3 2600+(OC)/2133(OC)/1866(OC)/1600/1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 16GB* - Supports Intel® Extreme Memory Profile (XMP) *Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 64Mb AMI UEFI Legal BIOS with GUI support - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree

diskontcomputer.com
Firma Matzner Michael e.U.
Traunuferstrasse 110
4052 Ansfelden, Austria

	- SMBIOS 2.3.1 Support - DRAM, PCH, CPU PLL, VTT Voltage Multi-adjustment - Supports I. O. T. (Intelligent Overclocking Technology)
Audio, Video und Netzwerk	
Grafik	- n/a
Audio	- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec) - Premium Blu-ray audio support
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtek RTL8111E - Supports Wake-On-LAN - Supports LAN Cable Detection - Supports Energy Efficient Ethernet 802.3az
Erweiterungsslots/Konnektivität	
Steckplätze	- 1 x PCI Express 2.0 x16 slot (blue @ x16 mode) - 3 x PCI Express 2.0 x1 slots - 2 x PCI slots
SATA3	- 2 x SATA3 6.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10, RAID 5 and Intel® Rapid Storage), NCQ, AHCI and "Hot Plug" functions
USB 3.0	- 2 x USB 3.0 ports by Etron EJ168A, support USB 1.0/2.0/3.0 up to 5Gb/s
Anschluss	- 5 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10, RAID 5 and Intel® Rapid Storage), NCQ, AHCI and Hot Plug functions - 2 x SATA3 6.0 Gb/s connectors - 1 x ATA133 IDE connector (supports 2 x IDE devices) - 1 x IR header - 1 x COM port header - 1 x HDMI_SPDIF header - 1 x Power LED header - CPU/Chassis/Power FAN connector - 24 pin ATX power connector - 8 pin 12V power connector - CD in header - Front panel audio connector - 3 x USB 2.0 headers (support 6 USB 2.0 ports) - 1 x Dr. Debug with LED
ATX-Blende	I/O Panel - 1 x PS/2 Mouse Port - 1 x PS/2 Keyboard Port - 1 x Coaxial SPDIF Out Port - 1 x Optical SPDIF Out Port - 6 x Ready-to-Use USB 2.0 Ports - 1 x eSATA2 Connector - 2 x Ready-to-Use USB 3.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - 1 x Clear CMOS Switch with LED - HD Audio Jack: Side Speaker / Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	
Einzigartige Features	- ASRock Extreme Tuning Utility (AXTU) - Instant Boot - ASRock Instant Flash - ASRock AIWI

diskontcomputer.com
Firma Matzner Michael e.U.
Traunuferstrasse 110
4052 Ansfelden, Austria

	- ASRock APP Charger - SmartView - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.) - Combo Cooler Option (C.C.O.) - Good Night LED - Turbo 40 / Turbo 50 Technology
Smart Switch	- 1 x Power Switch with LED - 1 x Reset Switch with LED - 1 x Clear CMOS Switch with LED
Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), ASRock Software Suite (CyberLink DVD Suite - OEM and Trial; Creative Sound Blaster X-Fi MB - Trial)
Produktzubehör	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA Data Cables (optional)
Hardware überwachung	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU/Chassis/Power Fan Tachometer - CPU/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU or MB Temperature) - CPU/Chassis Fan Multi-Speed Control - Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore
Formfaktor	- ATX Form Factor: 12.0-in x 8.6-in, 30.5 cm x 21.8 cm - All Solid Capacitor design (100% Japan-made high-quality Conductive Polymer Capacitors)
Betriebssystem	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant
Zertifizierungen	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko bürgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursachet werden sind wir nicht verantwortlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.